

MOBILE Printer

4inch printer *Porti-W25*



Features

- Pocket size(138 * 88 * 24mm)
- Light weight(340g) for true mobility.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec, MAX)
- Battery Indicator
- UART or TTL/IrDA or Bluetooth ver2.1 + EDR interface.
- USB interface
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.
- Microsoft Windows 98/ME/XP/2000 compatible

Applications

Mobile POS, Field sales and service, Transportation, Hospitality, Parking, Utility billing, Safety, Material management.

Specifications

Item	Specification
Printing method	Direct thermal line printing
Characters per line	92cpl
Characters size	Eng. : 9*24dots, 12*24dots Kor. : 16*24dots, [24*24dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	4-inch (104mm, 832 dots)
Paper speed	50 mm/sec (MAX)
Paper supplied	Thermal roll paper (117 mm wide, 25Ø)
Dimensions	138 * 88 * 24 mm
Weight	340g
Interface	· UART or TTL · IrDA Ver 1.0 or Bluetooth Ver2.1 + EDR · USB
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Receive buffer size	1M bytes
Battery	Rechargeable 7.4V DC , 1400mAh (Li-ion)
Battery duration	1 hour continuous printing
Battery charger	Input (100~250VAC, 50~60Hz) Output(8.4VDC/0.8A), 4hours full charge time



ROTHER GmbH . Fileitzen 11 . D29389 Bad Bodenteich
 Phone +49(0)5824 985-377 Fax +49(0)5824 985-378
 info@rother-elektronik.de www.rother-elektronik.de

