

3 INCH PORTABLE PRINTER

LK-P32

- ☑ Compact and rugged design
- ☑ Adjustable paper width from 44 ~ 79.5mm
- ☑ Flexible connectivity including USB, Bluetooth Class2
- ☑ Prints at 70mm per second



LK-P32

Product Image

TOP



LEFT



RIGHT



COVER OPEN



Specification

Model	LK-P32	
Printing Method	Direct Thermal	
Printing Speed	Max. 70mm/sec	
Resolution	203 DPI	
Character	9Type (bitmap font)	
Character Set	ALPHA NUMERIC Character, Extension Character	
Barcode	EAN-8, EAN-13, Code39, ITF, UPC-A, Codabar, Code93, Code128	
Emulation	ESC/POS, CPCL Command Compatible	
Driver	Windows CE 6.0, Windows Mobile6.0, Android	
Sensor	Paper End Sensor, Cover Open sensor, Black Mark Sensor, Gap Sensor	
Paper	Paper Type	Thermal Paper / Label
	Width	44 ~ 79.5 ±0.5mm
	Thickness	0.065 ~ 0.14mm
	External Diameter	Max. Φ40mm ±0.5mm
	Internal Diameter	18mm ±0.5mm
Reliability	TPH	50km
	Battery	Continuous Printing 40~50min Standby : 11hour
Communications	USB, Bluetooth Class2	
Battery Charger	Input	100 ~ 240V 50/60Hz 0.4A
	Output	8.4V 800mA 6.72W LPS
Battery	Battery Type	Li-ion
	Output	7.4V, 1500mAH
	Charging Time	2hours 30min
Size	W x D x H(mm)	109 x 104 x 48.5
	W x D x H(″)	4.29 x 4.09 x 1.9
Weight	335g (with battery)	
Temperature	Operation	-10 ~ 50 °C
	Storage	-20 ~ 60 °C
Humidity	Operation	35 ~ 95%
	Storage	10 ~ 95%



SEWOO TECH CO.,LTD.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

<http://www.miniprinter.com>

ROTHER GmbH

Fileitzen 11.

DE29389 Bad Bodenteich

T +49(0)5824-985-377

F +49(0)5824-985-378

info@rother-precision.de

www.rother-precision.de