

STYLISH AND INNOVATIVE 4 INCH RECEIPT/LABEL PORTABLE PRINTER

LK-P41

- High gloss cover and 3 color LEDs
- Adjustable paper width from 50.4mm to 112mm
- 2 types of battery selectable - 2200/4400mAh
- Large capacity, paper rolls up to 56mm(OD)
- Highly reliable Bluetooth communications or Wi-Fi(802.11b/g) available(Optional)
- ESC/POS, CPCL command compatible
- IP54(with case) certified

ROTHER



● SPECIFICATION

PRINT METHOD	Direct Thermal	
PRINTING SPEED (max)	80mm/sec	
DOT DENSITY	203DPI	
DOT PITCH	8 dots/mm, 0.125pitch	
EFFECTIVE PRINTING WIDTH	104mm, 832dots/line	
PAPER	TYPE	Thermal paper / Label
	WIDTH	50.4mm ~ 112mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. Ø 56.0mm
	ROLL CORE INNER DIAMETER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
FONTS and GRAPHICS	STANDATD FONTS	Seven resident fonts 12-48 pt.
	OPTIONAL	International character sets
	GRAPHICS, LINE AND BOX DRAWING	PCX and Bitmap
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	

EMULATION	ESC/POS, CPCL Command compatible	
DRIVER	Windows Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0~), Linux Printer Driver, Symbian, Blackberry, Android (2.1~)	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi(802.11b/g)
BATTERY CHARGER	External Charger(Output 8.4VDC / 0.8A)	
BATTERY	7.4V 2200mAh, 3.7Hrs charging time, 20Hrs stand-by	
DIMENSION	WxDxH(mm)	149 x 162 x 70
	WxDxH(inch)	5.87 x 6.37 x 2.75
WEIGHT	572g (with 2200mAh Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 95%
	STORAGE	10 ~ 95%

● APPLICATION



ROTHER

www.rother-precision.de