

# PANEL Printer

2inch printer **Porti-AP60**

**Auto cutting**



## Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec)
- UART or RS-485, Parallel interface.
- Auto cutting.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.



## Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems

## Specifications

Item	Specification
Printing method	Direct thermal line printing
Characters per line	42 cpl
Characters size	Eng : 9*24 dots, 12*24 dots / Kor : 16*24 dots [24*24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	2-inch (48 mm, 384 dots)
Paper speed	50 mm/sec (MAX)
Paper supplied	Thermal roll paper (57mm wide, 60Ø)
Dimensions	107.2 * 109.1 * 90.6 mm
Weight	451 g
Interface	UART or RS-485 or Parallel
Barcodes	PDF417, QR code, Data matrix (2-dimension), Code128, Code93, Code93, UPC, EAN(KAN, JAN), CODABAR
Receive buffer size	10K bytes
Input power	9VDC, Standby 60mA and Max 3A