

PANEL Printer

2inch printer **WSP-CP260/280**

Auto cutting



<WSP-CP260>



<WSP-CP280>

Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(200mm/sec)
- UART(RS-232C) interface.
- Auto cutting.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.

Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems

Specifications

Item	Specification
Printing method	Direct thermal line printing
Characters per line	48 cpl
Characters size	Eng : 9*24 dots, 12*24 dots / Kor : 16*24 dots [24*24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	2-inch (54 mm, 432 dots)
Paper speed	200 mm/sec (MAX)
Paper supplied	Thermal roll paper (CP260 : 57mm wide, 60Ø / CP280 : 57mm wide, 80Ø)
Dimensions	CP260 : 91.1x104.4x67.6mm / CP280 : 91.1x122.4x88.5mm
Interface	UART (RS-232C)
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Receive buffer size	1M bytes
Input power	24VDC, 3A OVER