

MOBILE Printer

2inch printer **Porti-SC40N**

MSR

Features

- Pocket size (80.5 * 113.5 * 46 mm)
- Light weight(300g) for true mobility.
- Very silent printing thru direct thermal printing method
- High speed (80mm/sec, MAX)
- UART or TTL, Bluetooth ver2.1 + EDR interface.
- Support magnetic Stripe Reader
- Support Graphic LCD (128*32 dots) with Backlight
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.

Applications

Mobile POS, Field sales and service, Transportation, Hospitality, Parking, Utility billing, Safety, Material management.

 **Bluetooth™**



Specifications

Item	Specification
Printing method	Direct thermal line printing
Characters per line	42cpl (MAX)
Characters size	Eng : 9*24 dots, 12*24 dots Kor : 16924 dots, [24*24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	2-inch (48mm, 384 dots)
Printing speed	80 mm/sec (MAX)
Dimensions	80.5 * 113.5 * 46 mm
Weight	300g
Interface	· UART or TTL · Bluetooth Ver2.1 + EDR
Paper supplied	Thermal roll paper (57mm wide, 40Ø)
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Receive buffer size	1M bytes
Battery	Rechargeable 7.4V DC , 1100mAh (Li-ion)
Battery duration	1 hour continuous printing
MSR	1&2 or 2&3 Track Reading
Battery charger	Input (100~250VAC, 50~60Hz) Output(8.4VDC/0.8A), 4hours full charge time

ROTHER

ROTHER GmbH . Fieitzten 11 . D29389 Bad Bodenteich
Phone +49(0)5824 985-377 Fax +49(0)5824 985-378
info@rother-elektronik.de www.rother-elektronik.de